



ELEMAX

Power of Next Generation

DEBUT!

VALUE SERIES



BRAND-NEW ! "ELEMAX VALUE SERIES"

FEATURES



Novel New Design "V-Frame"
"V-Frame" breaks a shell of the traditional generators



- New Development
"XV Alternator"



XV Alternator

- Light Weight -15% Down

SH3200EX: 44kg → SV2800: 38kg
SH7600EX: 78kg → SV6500: 66kg



- Fuel Tank Capacity - Up
- Over 12 hours
Continuous Operation Possible
[50Hz] SH3200EX: 14h → SV2800: 15h
[50Hz] SH7600EX: 8.5h → SV6500: 12h



Electric Key Starting System
Available to All Models



One Side Operation

You can operate all
(Control Panel & Starting
System) from One
Direction.



Made In Japan
Produced under a strict quality control
of Sawafuji Japan.



Optional Equipment Available

- 4-Wheel Kit
- Upper Bar



4 Wheel Kit



Upper Bar

SV2800S/SV3300S



Control Panel (Type: R, S)



- 1 Engine SW
- 2 V Meter
- 3 Consent
- 4 Pilot Lamp
- 5 Protector
- 6 Earth Terminal

Model	SV2800S/SV3300S	
Frequency (Hz)	50	60
Rated Output (kW)	2.0/2.5	2.3/2.8
Dry Weight (kg)	41/44	
Continuous Operating Hours (h)	15/12	13/10
Dimensions (mm) *with Battery Guard	W532 L623 H491	

	SV2800S		SV3300S	
50 Hz	Rated Output	2.0 kW	Rated Output	2.5 kW
	Continuous Operating Hours	15h	Continuous Operating Hours	12h
60 Hz	Rated Output	2.3 kW	Rated Output	2.8 kW
	Continuous Operating Hours	13h	Continuous Operating Hours	10h



SV2800S

*Battery is not included.

ELEMAX

Power of Next Generation

SV2800/SV3300



SV2800



Control Panel
(Type: R, S)

Model	SV2800/SV3300	
Frequency (Hz)	50	60
Rated Output (kW)	2.0/2.5	2.3/2.8
Dry Weight (kg)	38/41	
Continuous Operating Hours (h)	15/12	13/10
Dimensions (mm)	W438 L623 H491	

50 Hz

Rated Output
2.0 kW

Continuous Operating Hours
15h

Rated Output
2.5 kW

Continuous Operating Hours
12h

60 Hz

Rated Output
2.3 kW

Continuous Operating Hours
13h

Rated Output
2.8 kW

Continuous Operating Hours
10h



SV6500/SV6500S



SV6500S

*Battery is not included.



Control Panel (SV6500S)
(Type: R, S)

Model	SV6500/SV6500S	
Frequency (Hz)	50	60
Rated Output (kW)	5.0	5.5
Dry Weight (kg)	66/68	
Continuous Operating Hours (h)	12	9
Dimensions (mm)	W548 L708 H513	

50 Hz

Rated Output
5.0 kW

Continuous Operating Hours
12h

60 Hz

Rated Output
5.5 kW

Continuous Operating Hours
9h



(SV6500S)

SPECIFICATION

MODEL			SV2800(S)		SV3300(S)		SV6500(S)			
TYPE			50Hz=R: 220V, 60Hz=S: 220V, D: 110/220V, LD: 120/240V							
Frequency			Hz		50	60	50	60	50	60
ENGINE	Models		V210		V225		V420			
	Displacement		CC		212		223		420	
	Rated Power	3000rpm	kW		3.0		3.5		6.6	
GENERATOR	Type		Air cooled 4-stroke OHV							
	Oil Alert System		Yes							
	Type		2-pole, Field Rotating							
	Voltage Regulation System		AVR							
	Output	Rated	kW	2.0	2.3	2.5	2.8	5.0	5.5	
		Maximum	kW	2.3	2.8	2.9	3.3	5.5	6.5	
	Rated Voltage		R: 220V-50Hz, S: 220V-60Hz, D: 110/220V-60Hz, LD: 120/240V-60Hz							
DC Output (V-A)		No								
Power Factor		COS 1.0								
OTHERS	Warning Lamps		No							
	Fuel Tank Capacity		L	20	20	35				
	Dimensions (mm)	L	623	623	708					
		W	438 (532*)	438 (532*)	548					
		H	491	491	513					
	Dry Weight		kg	38 (41)	41 (44)	66 (68)				
	Sound Level 7m Rated Load		dB	69	72	70	74	75	80	
	Continuous Operating Hours		h	15	13	12	10	12	9	
Starting System		Recoil (Key Starter)		Recoil (Key Starter)		Recoil (Key Starter)				

Specifications are subject to change without notice.

VALUE SERIES





CAUTION
Without this label
FAKE!

How to Authenticate ELEMEX Generators

Check Point 1 -TRUSTGRAM-
Make sure that the security label of "TRUSTGRAM" is put on the product body.



Check Point 2 -HOLOGRAM-
Make sure that the following change is visible through the "VIEWER".



SAWAFUJI ELECTRIC CO., LTD.

3, Nittahayakawa-cho, Ota-City,
Gunma 370-0344 JAPAN
PHONE: +81-276-56-7139
FAX: +81-276-56-6075
URL: <http://www.elemax.jp>

